

Datum: 11.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

L-obročni del, na votli vijak G 3/8, zun. Ø 10 mm

Kategorija: [L-ring nipple](#)
Šifra: **108841RIE**

Kratek opis

L-ring piece, for hollow screw G 3/8, for hose exterior Ø 10,
Working pressure -0.98 to 16 bar, Operating temp. -20 °C to
70 °C

The advanced version of our highly successful push-in
fittings series manufactured in nickel-plated brass.

Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose,
even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. delovni tlak [bar]	-0.98
Material	Nickel-plated brass
Priporočena cev	PA, PU
Rokav	Black nickel-plated brass
Serijska	click-clock
Vpenjalni obroč	Stainless steel
Za banjo vijak	G 3/8
Za cevi O.D. [mm]	10
Max. delovni tlak [bar]	16
L2 [mm]	20.0
L1 [mm]	28.0
Max. delovna temperatura [°C]	70