

Datum: 11.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



Mali naoljevalnik, G 1/4, Operating pressure 2 - 15 bar

Kategorija: [Mini oil-mist lubricator](#)
Šifra: **101527RIE**

(slika je simbolična)

Kratek opis

Mini mist oiler, G 1/4, Operating pressure 2 - 15 bar, Medium / ambient temp. max. 50 °C, Oil container made of polycarbonate

For mounting on pneumatic impact tools (nail drivers, tackers, screwdrivers) which work intermittently.

Also suitable for tools with continuous compressed air demand (grinding and polishing machines).

Fixed drip rate: Approx. 0.4 cm³ per 100 work cycles, one filling = 3000 work cycles.

Oil consumption in continuous operation (at 6 bar): 0.15 cm³ / Nm³ (varies depending on ambient temperature and oil used).

Tehnične Specifikacije

Navoj	G 1/4
Posoda za olje	Polycarbonate
Razred olja	CL 32 acc. to DIN
Smer pretoka	any
Vgradni položaj	Oil intake at the lowest point
Min. obratovalni tlak [bar]	2
DN	8
Max. obratovalni tlak [bar]	15
A [mm]	33.0
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
B [mm]	60.0