

Datum: 13.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

MikroFilter brez diferenčnega manometra, 0.01 µm, G 1/4

Kategorija: [Microfilter without differential pressure gauge](#)
Šifra: **101568RIE**

Kratek opis

Microfilter without differential pressure gauge, 0.01 µm, G 1/4, Input pressure 4 - 12 bar, Medium / ambient temp. 5 °C to 60 °C
Ideal for filtering out aerosols and solid impurities larger than 0.01 µm.
Micro-filters should always be used in conjunction with a pre-filter.

Tehnične Specifikacije

Element filtra	Borosilicate (with glass-fibre material and foam plastic) At $P_1 = 6$ bar and pressure drop $\Delta_p = 1.5\%$
Merjenje pretoka	G 1/4
Navoj	Aluminium
Ohišje	Aluminium
Posoda filtra	0.01
Rang filtra [µm]	4
Min. vhodni tlak [bar]	5
Min. sobna temperatura [°C]	5
Min. temperatura medija [°C]	12
Max. vhodni tlak [bar]	57.0
C [mm]	60
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	83.0
A [mm]	99.9999
Učinkovitost [%]	335.0
B2 [mm]	353.0
D [mm]	1300
Pretok [l/min]	