



MikroFilter»FUTURA«Kov. pos.0.01 µm, Vel.1, G 1/4, FA

Kategorija: [Microfilter with metal bowl and sight glass](#)
Šifra: **156576RIE**

(slika je simbolična)

Kratek opis

Microfilter »FUTURA«, Metal container and viewing tube, 0.01 µm, Size 1, G 1/4, 1.5-16 bar, Temp. -10 °C to 50 °C, Fully-automatic

Micro-filters in modern design for compliance with strict compressed air purity requirements.

Micro-filters are used to separate solid oil, water and solid impurities as small as 0.01 µm from compressed air and gases.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Borosilicate glass fibre
Ločevanje prahu	> 0.01 µm 99.999 % At P ₂ = 6 bar and pressure drop Δ _p = 0.1 bar
Merjenje pretoka	G 1/4 Fully-automatic
Navoj	PA66 GF60
Odtok kondenzata	Metal container with viewing tube
Ohišje	Material: Die-cast zinc
Posoda	FUTURA
Priključni navoj	Compressed air, neutral gases
Serijska	
Srednje	
Vsebnost olja v ostanku [mg/m ³]	< 0.01
Rang filtra [µm]	0.01
Velikost	1
Min. vhodni tlak [bar]	1.5
Max. vhodni tlak [bar]	16
C [mm]	39.5
Max. temperaturno območje [°C]	50
A [mm]	52.0
B [mm]	186.5
Pretok [l/min]	350