

Datum: 12.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Naoljevalnik »G«PC zbir.Zašč. kletkaVel. 400G 3/8

Kategorija: [Oil-mist lubricator with PC bowl, bowl guard](#)  
Šifra: **116446RIE**

### Kratek opis

Mist oiler »G«, PC container, Protective cage, Mounting bracket, Size 400, G 3/8, Input pres. max. 10 bar, Working pres. 0.5-9 bar  
Proportional lubricators, oil can be filled under pressure.

### Tehnične Specifikacije

|                              |                                                                      |
|------------------------------|----------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 3/8                                                                |
| Ohišje                       | Die-cast aluminium                                                   |
| Posoda                       | Polycarbonate container with protective cage                         |
| Serija                       | G                                                                    |
| Tesnilo                      | NBR                                                                  |
| Vidna kupola                 | Brass/POM                                                            |
| Vzmet pokrova motorja        | POM                                                                  |
| Min. delovni tlak [bar]      | 0.5                                                                  |
| Max. delovni tlak [bar]      | 9                                                                    |
| Max. vhodni tlak [bar]       | 10                                                                   |
| C [mm]                       | 48.0                                                                 |
| A [mm]                       | 68.0                                                                 |
| Max. sobna temperatura [°C]  | 70                                                                   |
| Max. temperatura medija [°C] | 70                                                                   |
| D [mm]                       | 142.0                                                                |
| B [mm]                       | 190.0                                                                |
| Velikost                     | 400                                                                  |
| Pretok [l/min]               | 7500                                                                 |