

Datum: 12.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



Naoljevalnik »variobloc«PC zbir.Protec. cageVel.2,G 1/2

Kategorija: [Oil-mist lubricator with PC bowl and bowl guard](#)
Šifra: **124818RIE**

(slika je simbolična)

Kratek opis

Mist oiler »variobloc«, PC container, protective cage, Size 2, G 1/2, Input pressure max. 16 bar, Medium / ambient temp. max. 50°C

Proportional lubricators, oil can be filled under pressure.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/2
Ohišje	Die-cast zinc
Posoda	Polycarbonate container with protective cage
Razred olja	CL 32 acc. to DIN 51517-ISO VG 32
Serija	variobloc
Tesnilo	NBR
Vidna kupola	PA
Velikost	2
Max. vhodni tlak [bar]	16
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
C [mm]	57.0
A [mm]	70.0
B [mm]	224.0
Pretok [l/min]	4600