



(slika je simbolična)

Natančen tlačni regulator, Pneumat. daljinsko vodeni, G 1/2

Kategorija: [Precision pressure regulators](#)
Šifra: **101258RIE**

Kratek opis

Precision pressure regulator, Pneumatically remote controlled via external pilot control valve, G 1/2, Control range 0.05 - 7 bar
With high flow rate and large secondary venting.
Pneumatically controlled diaphragm pressure regulators with large secondary venting
for applications requiring an extremely accurate working pressure, especially at high flow rates.
We recommend our »multifix« series of pilot controllers.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 5 \text{ bar}$, $P_2 = 3 \text{ bar}$ and pressure drop $\Delta p \leq 0,1 \text{ bar}$
Nadzor zraka	G 1/8
Navoj	G 1/2
Navoj manometra	G 1/4
Odzračevalni vtič	G 3/8 (for mounting a silencer)
Ohišje	Die-cast zinc, painted black
Poraba zraka	Yes
Srednje	Micro-filtered, unoiled compressed air (0.01 μm)
Tesnilo	NBR
Min. krmilno območje [bar]	0.05
Max. notranja poraba zraka	6 l/min (depending on secondary pressure)
Max. krmilno območje [bar]	7
Max. vodeni tlak [bar]	10
Max. vhodni tlak [bar]	16
D [mm]	43.5
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	64.5
A [mm]	82.0
B [mm]	108.0
Pretok	3000 l/min