

Datum: 11.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Navojni vtični priključek, G 1/8 o. vtični prikllop Ø 4 mm

Kategorija: [Push-in plug, parallel male thread with O-ring](#)
Šifra: **135293RIE**

Kratek opis

Thread plug nipple, G 1/8 o. , Plug connenction Ø 4 mm,
Stainless steel 1.4404

For use in more aggressive environments and corrosive media.

Only recommended for use in combination with stainless steel quick connectors type 844 ff. Suitability testing for use with other series is the responsibility of the user.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Min. delovni tlak [bar]	-0.98
Material	Stainless steel 1.4404
Navoj	G 1/8
Primerni materiali za cevi	PVDF, PTFE, PA, PU
Standardni navoj	DIN EN ISO 228-1
Tesnilo	FPM
Priključek [mm]	4
a/f [mm]	14
Max. delovni tlak [bar]	20
L1 [mm]	34.8
Max. delovna temperatura [°C]	150
Max. temperatura medija [°C]	150