

Datum: 13.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Okrogli cilinder, delujoč v dveh smereh, bat Ø 32, hod 50, G 1/8

Kategorija: [Metalwork](#)  
Šifra: **105848RIE**

### Kratek opis

Round cylinder, double-acting, with magnet, Piston Ø 32, Stroke 50, G 1/8, Working pressure max. 10 bar, Temp. -10 °C to 80 °C  
Version with magnetic piston.  
Suitable for filtered (50 µm), unlubricated or lubricated compressed air.  
If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                |                                                        |
|--------------------------------|--------------------------------------------------------|
| Min. temperaturno območje [°C] | -10                                                    |
| Bat                            | Technopolymer                                          |
| Batnica                        | C45 steel, hard chrome-plated                          |
| Cushioning                     | non-cushioned                                          |
| Ffunkcija                      | double-acting                                          |
| Gewinde Kolbenstange           | male piston rod                                        |
| Magnet                         | with magnet                                            |
| Navoj na batnici               | M10x1.25                                               |
| Oblika                         | Screwed joint between stainless steel barrel and heads |
| Ovoj                           | Anodised aluminium                                     |
| Povezava                       | G 1/8                                                  |
| Tesnilo                        | NBR                                                    |
| Min. nastavljeni tlak [bar]    | 0.4                                                    |
| Max. delovni tlak [bar]        | 10                                                     |
| Bat Ø [mm]                     | 32                                                     |
| Stroke [mm]                    | 50                                                     |
| Max. temperaturno območje [°C] | 80                                                     |