

Datum: 13.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Okrogli cilinder, delujoč v dveh smereh, bat Ø 50, hod 125, G 1/4

Kategorija: [Metalwork](#)  
Šifra: **105873RIE**

### Kratek opis

Round cylinder, double-acting, with magnet, Piston Ø 50, Stroke 125, G 1/4, Working pressure max. 10 bar, Temp. -10 °C to 80 °C  
Version with magnetic piston.  
Suitable for filtered (50 µm), unlubricated or lubricated compressed air.  
If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                |                                                      |
|--------------------------------|------------------------------------------------------|
| Min. temperaturno območje [°C] | -10                                                  |
| Bat                            | Technopolymer                                        |
| Batnica                        | C45 steel, hard chrome-plated                        |
| Cushioning                     | non-cushioned                                        |
| Ffunkcija                      | double-acting                                        |
| Gewinde Kolbenstange           | male piston rod                                      |
| Magnet                         | with magnet                                          |
| Navoj na batnici               | M16x1.5                                              |
| Oblika                         | Screw joint between stainless steel barrel and heads |
| Ovoj                           | Anodised aluminium                                   |
| Povezava                       | G 1/4                                                |
| Tesnilo                        | NBR                                                  |
| Min. nastavljeni tlak [bar]    | 0.3                                                  |
| Max. delovni tlak [bar]        | 10                                                   |
| Bat Ø [mm]                     | 50                                                   |
| Max. temperaturno območje [°C] | 80                                                   |
| Stroke [mm]                    | 125                                                  |