

Datum: 13.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Okrogli cilinder, delujoč v dveh smereh, bat Ø 50, hod 500, G 1/4

Kategorija: [Metalwork](#)
Šifra: **105879RIE**

Kratek opis

Round cylinder, double-acting, with magnet, Piston Ø 50, Stroke 500, G 1/4, Working pressure max. 10 bar, Temp. -10 °C to 80 °C
Version with magnetic piston.
Suitable for filtered (50 µm), unlubricated or lubricated compressed air.
If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Bat	Technopolymer
Batnica	C45 steel, hard chrome-plated
Cushioning	non-cushioned
Ffunkcija	double-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Navoj na batnici	M16x1.5
Oblika	Screwed joint between stainless steel barrel and heads
Ovoj	Anodised aluminium
Povezava	G 1/4
Tesnilo	NBR
Min. nastavljeni tlak [bar]	0.3
Max. delovni tlak [bar]	10
Bat Ø [mm]	50
Max. temperaturno območje [°C]	80
Stroke [mm]	500