

Datum: 12.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Okrogli cilinder, enosmerni, bat Ø 12, hod 10, M5

Kategorija: [Metalwork](#)  
Šifra: **105828RIE**

### Kratek opis

Round cylinder, ISO 6432, single-acting, Magnet, Piston Ø 12, Stroke 10, M5, Working pressure max. 10 bar, Temp. -10 °C to 80 °C

Single and double-acting cylinders, with magnetic piston. Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                |                                                        |
|--------------------------------|--------------------------------------------------------|
| Min. temperaturno območje [°C] | -10                                                    |
| Bat                            | Synthetic (acetal) resin                               |
| Batnica                        | C45 steel, hard chrome-plated                          |
| Cushioning                     | non-cushioned                                          |
| Ffunkcija                      | single-acting                                          |
| Gewinde Kolbenstange           | male piston rod                                        |
| Magnet                         | with magnet                                            |
| Navoj na batnici               | M6                                                     |
| Oblika                         | Flanged joint between stainless steel barrel and heads |
| Ovoj                           | Stainless steel 1.4301                                 |
| Povezava                       | M5                                                     |
| Standard                       | acc. to ISO 6432                                       |
| Starting position              | pressureless in the retracted position                 |
| Tesnilo                        | NBR                                                    |
| Min. nastavljeni tlak [bar]    | 0.8                                                    |
| Max. delovni tlak [bar]        | 10                                                     |
| Stroke [mm]                    | 10                                                     |
| Bat Ø [mm]                     | 12                                                     |
| Max. temperaturno območje [°C] | 80                                                     |