

Datum: 11.05.2024



(slika je simbolična)

## Predfiltrirajte z diferenčnim manometrom, 3 µm, G 3/4

Kategorija: [Pre-filter with differential pressure gauge](#)Šifra: **101547RIE**

### Kratek opis

Pre-filter with differential pressure gauge, 3 µm, G 3/4, Input pressure 4 - 12 bar, Medium / ambient temperature 5 °C to 60 °C

For filtering out solid impurities larger than 3 µm and for moisture separation.

For connection upstream of a micro-filter or a combination micro-filter/activated carbon filter.

### Tehnične Specifikacije

|                                                   |                                                       |
|---------------------------------------------------|-------------------------------------------------------|
| Element filtra                                    | Polyethylene (with 45% cavity)                        |
| Ločevanje delcev [µm]                             | from 3                                                |
| Merjenje pretoka                                  | At $P_1 = 6$ bar and pressure drop $\Delta p = 0.5\%$ |
| Navoj                                             | G 3/4                                                 |
| Ohišje                                            | Aluminium                                             |
| Posoda filtra                                     | Aluminium                                             |
| Max. označeni razpon diferenčnega manometra [bar] | 2                                                     |
| Rang filtra [µm]                                  | 3                                                     |
| Min. vhodni tlak [bar]                            | 4                                                     |
| Min. sobna temperatura [°C]                       | 5                                                     |
| Min. temperatura medija [°C]                      | 5                                                     |
| Max. vhodni tlak [bar]                            | 12                                                    |
| C [mm]                                            | 57.0                                                  |
| Max. sobna temperatura [°C]                       | 60                                                    |
| Max. temperatura medija [°C]                      | 60                                                    |
| A [mm]                                            | 83.0                                                  |
| Učinkovitost [%]                                  | 99.99                                                 |
| B2 [mm]                                           | 405.0                                                 |
| D [mm]                                            | 493.0                                                 |
| B1 [mm]                                           | 502.5                                                 |
| Pretok [l/min]                                    | 2000                                                  |