

## Pregrade armatklak POM, G 1/2 za cev zunanji Ø 10 mm



Kategorija: [Bulkhead connectors - POM](#)  
Šifra: **135974RIE**

(slika je simbolična)

### Kratek opis

Bulkhead fitting POM, G 1/2, for hose exterior Ø 10 mm, working pressure -0.95 to 10 bar  
Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications.  
All our push-in fittings made of POM have the following approvals:  
drinking water DVGW, KTW, FDA and NSF.  
Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

### Tehnične Specifikacije

|                                       |                      |
|---------------------------------------|----------------------|
| Min. delovna temperatura v zraku [°C] | -20                  |
| Min. delovni tlak [bar]               | -0.95                |
| Material                              | Acetal polymer (POM) |
| Navoj                                 | G 1/2                |
| Min. delovna temperatura v vodi [°C]  | 1                    |
| Max. delovni tlak [bar]               | 10                   |
| Za cevi O.D. [mm]                     | 10                   |
| a/f [mm]                              | 22                   |
| L1 [mm]                               | 41.0                 |
| Max. delovna temperatura v zraku [°C] | 65                   |
| Max. delovna temperatura v vodi [°C]  | 70                   |