

Datum: 13.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Prenosni krogelni ventil za vodo, Z ročico, ročni, IT/IT, Rp 1/4

Kategorija: [Potable water ball valves](#)  
Šifra: **103406RIE**

### Kratek opis

Potable water ball valve, Manual lever, IT/IT, Brass chrome plated, Operating temp. -20 °C to 150 °C, Rp 1/4, DN 8, PN max. 50 bar  
Brass ball valve with free flow, DVGW approved. This valve complies with the European standard EN 13828 and the working paper DVGW W 570, and is therefore approved for use with drinking water. The special ball technology prevents bacteria from forming inside the valve if it is not in use for a long period of time (i.e. the valve is absolutely safe for drinking water).

### Tehnične Specifikacije

|                               |                                  |
|-------------------------------|----------------------------------|
| Min. delovna temperatura [°C] | -20                              |
| Aplikacije                    | Potable water, water             |
| DVGW odobritev                | DIN EN 13828:2003-12, DVGW W 570 |
| Krogelno tesnilo              | PTFE                             |
| Krogla                        | Chrome-plated brass              |
| Navoj                         | Rp 1/4                           |
| Ohišje                        | Chrome-plated brass              |
| Ročica                        | Steel with plastic coating       |
| Standardni navoj              | Thread acc. to ISO 7-1           |
| Stebelno tesnilo              | NBR / FKM                        |
| DN                            | 8                                |
| E [mm]                        | 11.0                             |
| a/f [mm]                      | 18                               |
| B [mm]                        | 41.8                             |
| L [mm]                        | 49.5                             |
| PN [bar]                      | 50                               |
| A [mm]                        | 85.5                             |
| Max. delovna temperatura [°C] | 150                              |