



(slika je simbolična)

## Ravni navojni priključek Ž G 3/8 i., za cev 4/6 mm, AF 22, PA

Kategorija: [Female connector with female G thread](#)  
Šifra: **110787RIE**

### Kratek opis

Straight screw-on fitting G 3/8 i., for hose 4/6 mm, AF 22, Working pressure max. 10 bar (20 °C)/max. 1 bar (60 °C), PA  
Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzine, diesel oil, fuel oil and alkalis. Not suitable for use with acids.

### Tehnične Specifikacije

|                                    |                    |
|------------------------------------|--------------------|
| Narezana matica                    | Polypropylene (PP) |
| Navoj                              | G 3/8              |
| Telo vijačnega priključka          | Polyamide (PA)     |
| Vpenjalni obroč                    | Polypropylene (PP) |
| Max. delovni tlak pri 60 ° C [bar] | 1                  |
| Za cevi [mm]                       | 4/6                |
| Max. delovni tlak pri 20 ° C [bar] | 10                 |
| L2 [mm]                            | 17.0               |
| a/f [mm]                           | 22                 |
| L1 [mm]                            | 36.0               |