



(slika je simbolična)

## Ravni pot.i fitting G 1/4 , zun. premera 4 mm

Kategorija: [Male connector, parallel male thread, outer hex](#)

Šifra: **135062RIE**

### Kratek opis

Straight push-in fitting, Exterior hexagonal, G 1/4 o. for hose exterior Ø 4 mm, Working pressure -0.98 - 20 bar, 1.4404  
For use in more aggressive environments and corrosive media.

The suitability test for the individual application is the user's responsibility.

### Tehnične Specifikacije

|                               |                    |
|-------------------------------|--------------------|
| Min. delovna temperatura [°C] | -20                |
| Min. temperatura medija [°C]  | -20                |
| Min. delovni tlak [bar]       | -0.98              |
| Material                      | Stainless steel    |
|                               | 1.4404             |
| Navoj                         | G 1/4              |
| Primerni materiali za cevi    | PVDF, PTFE, PA, PU |
| Standardni navoj              | DIN EN ISO 228-1   |
| Tesnilo                       | FPM                |
| Za cevi O.D. [mm]             | 4                  |
| a/f [mm]                      | 17                 |
| Max. delovni tlak [bar]       | 20                 |
| L1 [mm]                       | 23.8               |
| Max. delovna temperatura [°C] | 150                |
| Max. temperatura medija [°C]  | 150                |