



(slika je simbolična)

## Ravni potisni fitting, G 3/8 o., Za cev zunanji Ø 10 mm

Kategorija: [Male connector, parallel male thread, outer hex](#)

Šifra: **110366RIE**

### Kratek opis

Straight push-in fitting, Exterior hexagonal, G 3/8 o., for hose exterior Ø 10 mm, Working pressure max. 15 bar, Stainless steel

For use with aggressive media and in areas susceptible to corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

### Tehnične Specifikacije

|                               |                           |
|-------------------------------|---------------------------|
| Min. delovna temperatura [°C] | -20                       |
| Min. temperatura medija [°C]  | -20                       |
| Material                      | Stainless steel<br>1.4404 |
| Navoj                         | G 3/8                     |
| Primerni materiali za cevi    | PVDF, PTFE, PA, PU        |
| Standardni navoj              | DIN EN ISO 228-1          |
| Delovni tlak pulzira [bar]    | 10                        |
| Za cevi O.D. [mm]             | 10                        |
| Max. delovni tlak [bar]       | 15                        |
| a/f [mm]                      | 17                        |
| L1 [mm]                       | 24.7                      |
| Max. delovna temperatura [°C] | 150                       |
| Max. temperatura medija [°C]  | 150                       |