

Datum: 13.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Ravni potisni fitting »Metallica« R 1/8 o., Cev zunanja Ø 6

Kategorija: [Male connector, conical ET, coated with outer hex](#)  
Šifra: **108883RIE**

### Kratek opis

Straight push-in fitting »metallica«, R 1/8 o., for hose exterior Ø 6 mm, Working pressure -0.98 to 16 bar, nickel-plated brass

All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion

### Tehnične Specifikacije

|                               |                                                            |
|-------------------------------|------------------------------------------------------------|
| Min. delovna temperatura [°C] | -20                                                        |
| Min. delovni tlak [bar]       | -0.98                                                      |
| Material                      | Nickel-plated brass                                        |
| Navoj                         | R 1/8                                                      |
| Priporočena cev               | PA and PU                                                  |
| Rokav                         | Nickel-plated brass                                        |
| Serijska                      | metallica                                                  |
| Vpenjalni obroč               | Male connector, conical male thread, coated with outer hex |
| Za cevi O.D. [mm]             | 6                                                          |
| a/f [mm]                      | 11                                                         |
| Max. delovni tlak [bar]       | 16                                                         |
| L1 [mm]                       | 24.5                                                       |
| Max. delovna temperatura [°C] | 150                                                        |