

Datum: 12.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Ravni vtični konekt. Metallica,

Kategorija: [Reducers with push-in plug](#)  
Šifra: **108996RIE**

### Kratek opis

Straight push-in connector »metallica«, Plug nipple reducing 10 mm, for hose exterior Ø 8 mm, Working pressure -0.98 to 16 bar

All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion; all fittings in this series can thus also be used at high temperatures (medium compressed air).

Only recommended for use in combination with quick connectors of the »metallica« series. Suitability testing for use with other series is the responsibility of the user.

### Tehnične Specifikacije

|                               |                            |
|-------------------------------|----------------------------|
| Min. delovna temperatura [°C] | -20                        |
| Min. delovni tlak [bar]       | -0.98                      |
| Material                      | Nickel-plated brass        |
| Priporočena cev               | PA and PU                  |
| Rokav                         | Nickel-plated brass        |
| Serijska                      | metallica                  |
| Vpenjalni obroč               | Reducers with push-in plug |
| Za cevi O.D. [mm]             | 8                          |
| Priključek [mm]               | 10                         |
| Max. delovni tlak [bar]       | 16                         |
| L1 [mm]                       | 38.5                       |
| Max. delovna temperatura [°C] | 150                        |