

Datum: 11.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Ravni vtični konekt. Metallica,

Kategorija: [Reducers with push-in plug](#)
Šifra: **108995RIE**

Kratek opis

Straight push-in connector »metallica«, Plug nipple reducing 8 mm, for hose exterior Ø 6 mm, Working pressure -0.98 to 16 bar

All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion; all fittings in this series can thus also be used at high temperatures (medium compressed air).

Only recommended for use in combination with quick connectors of the »metallica« series. Suitability testing for use with other series is the responsibility of the user.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. delovni tlak [bar]	-0.98
Material	Nickel-plated brass
Priporočena cev	PA and PU
Rokav	Nickel-plated brass
Serijska	metallica
Vpenjalni obroč	Reducers with push-in plug
Za cevi O.D. [mm]	6
Priključek [mm]	8
Max. delovni tlak [bar]	16
L1 [mm]	32.5
Max. delovna temperatura [°C]	150