



(slika je simbolična)

Serv. enota 2-delna »FUTURA« Kov. Vel.2, G 3/8, 0.1-1 Avt.

Kategorija: [Service unit, 2-piece with metal bowl, sight glass](#)
Šifra: **152430RIE**

Kratek opis

Service unit 2-part »FUTURA« with metal container, Viewing tube and pressure gauge, Size 2, G 3/8, Control range 0.1-1 bar, Fully
Two-piece service units with excellent flow rates in modern design.
Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Membrane	NBR
	At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar
Merjenje pretoka	G 3/8
Navoj	Fully-automatic
Odtok kondenzata	PA66 GF60
Ohišje	Metal container with viewing tube
Posoda	Material: Die-cast zinc
Priključni navoj	FUTURA
Serijska	Compressed air, neutral gases
Srednje	NBR
Tesnilo	PC
Vidna kupola	0.1
Min. krmilno območje [bar]	1
Max. krmilno območje [bar]	1.5
Min. vhodni tlak [bar]	1.6
Zaslon manometra max. [bar]	2
Velikost	5
Rang filtra [µm]	16
Max. vhodni tlak [bar]	50
Max. temperaturno območje [°C]	110.0
C [mm]	126.0
A [mm]	277.0
B [mm]	3500
Pretok [l/min]	