



## Serv. enota 2-delna»FUTURA«Kov.Vel.2, G3/8, 0.5-16 Pol avto.

Kategorija: [Service unit, 2-piece with metal bowl, sight glass](#)  
Šifra: **139561RIE**

(slika je simbolična)

### Kratek opis

Service unit 2-part »FUTURA« with metal container, Viewing tube and pressure gauge, Size 2, G 3/8, Control range 0.5-16 bar, Semi  
Two-piece service units with excellent flow rates in modern design.  
Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

### Tehnične Specifikacije

|                                |                                   |
|--------------------------------|-----------------------------------|
| Min. temperaturno območje [°C] | -10                               |
| Element filtra                 | Cellpor (PE)                      |
| Membrane                       | NBR                               |
|                                | At $P_1 = 10$ bar, $P_2 = 6.3$    |
| Merjenje pretoka               | bar and pressure drop             |
|                                | $\Delta_p = 1$ bar                |
| Navoj                          | G 3/8                             |
| Odtok kondenzata               | Semi-automatic                    |
| Ohišje                         | PA66 GF60                         |
| Posoda                         | Metal container with viewing tube |
| Priključni navoj               | Material: Die-cast zinc           |
| Serijska                       | FUTURA                            |
| Srednje                        | Compressed air, neutral gases     |
| Tesnilo                        | NBR                               |
| Vidna kupola                   | PC                                |
| Min. krmilno območje [bar]     | 0.5                               |
| Min. vhodni tlak [bar]         | 1.5                               |
| Velikost                       | 2                                 |
| Rang filtra [µm]               | 5                                 |
| Max. krmilno območje [bar]     | 16                                |
| Max. vhodni tlak [bar]         | 16                                |
| Zaslon manometra max. [bar]    | 25                                |
| Max. temperaturno območje [°C] | 50                                |
| C [mm]                         | 110.0                             |
| A [mm]                         | 126.0                             |
| B [mm]                         | 261.0                             |
| Pretok [l/min]                 | 3500                              |