



(slika je simbolična)

Serv. enota 2-delna »FUTURA« PC Vel.2, G1/2, 0.2-4, Pol avto.

Kategorija: [Service unit, 2-piece with PC bowl and bowl guard](#)
Šifra: **139553RIE**

Kratek opis

Service unit 2-part »FUTURA« with PC container, Protective cage and pressure gauge, Size 2, G 1/2, Control range 0.2 - 4 bar, Semi
Two-piece service units with excellent flow rates in modern design.
Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Membrane	NBR
Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/2
Odtok kondenzata	Semi-automatic
Ohišje	PA66 GF60
Posoda	Polycarbonate container with protective cage
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Vidna kupola	PC
Min. krmilno območje [bar]	0.2
Min. vhodni tlak [bar]	1.5
Velikost	2
Max. krmilno območje [bar]	4
Rang filtra [µm]	5
Zaslon manometra max. [bar]	6
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
C [mm]	110.0
A [mm]	126.0
B [mm]	257.0
Pretok [l/min]	3500