



(slika je simbolična)

## Serv. enota 2-delna »GA« Kov. pos.5 µm, Vel. 600, G 3/4

Kategorija: [Service unit, 2-piece with metal bowl, sight glass](#)  
Šifra: **178503RIE**

### Kratek opis

Service unit 2-part »GA«, Metal container, Viewing tube, 5 µm, Size 600, G3/4, Input pressure max. 10 bar, Control range 1.5-9 bar

Two-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

### Tehnične Specifikacije

|                                |                                                                      |
|--------------------------------|----------------------------------------------------------------------|
| Min. temperaturno območje [°C] | -5                                                                   |
| Merjenje pretoka               | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                          | G 3/4                                                                |
| Odtok kondenzata               | Fully-automatic                                                      |
| Ohišje                         | Die-cast aluminium                                                   |
| Posoda                         | Metal container with viewing tube                                    |
| Serija                         | GA                                                                   |
| Tesnilo                        | NBR                                                                  |
| Vidna kupola                   | Brass/POM                                                            |
| Vzmet pokrova motorja          | POM                                                                  |
| Min. krmilno območje [bar]     | 1.5                                                                  |
| Rang filtra [µm]               | 5                                                                    |
| Max. krmilno območje [bar]     | 9                                                                    |
| Max. vhodni tlak [bar]         | 10                                                                   |
| Max. temperaturno območje [°C] | 70                                                                   |
| C [mm]                         | 131.5                                                                |
| D [mm]                         | 205.0                                                                |
| A [mm]                         | 206.0                                                                |
| B [mm]                         | 336.5                                                                |
| Velikost                       | 600                                                                  |
| Pretok [l/min]                 | 6000                                                                 |