



(slika je simbolična)

Serv. enota 2-delna »multifix«Kov. pos.Vel. 5G 1

Kategorija: [Service unit, 2-piece with metal bowl, sight glass](#)
Šifra: **100580RIE**

Kratek opis

Service unit 2-part »multifix«, Metal container, Viewing tube, Size 5, G 1, Input pressure max. 20 bar, Control range 0.5 - 10 bar
Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6,3$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1
Odtok kondenzata	Semi-automatic
Ohišje	Aluminium
Posoda	Metal container with viewing tube
Serijska	multifix
Tesnilo	NBR
Vidna kupola	Zinc-glass-NBR
Vzmet pokrova motorja	POM-brass
Min. krmilno območje [bar]	0.5
Velikost	5
Max. krmilno območje [bar]	10
Zaslona manometra max. [bar]	16
Max. vhodni tlak [bar]	20
DN	25
Rang filtra [μ m]	40
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	128.0
A [mm]	200.0
D [mm]	255.7
B [mm]	383.7
Pretok [l/min]	13500