



## Serv. enota 3-delna »FUTURA« Kov. Vel. 2, G1/2, 0.5-10 Pol avto.

Kategorija: [Service unit, 3-piece with metal bowl, sight glass](#)  
Šifra: **139588RIE**

(slika je simbolična)

### Kratek opis

Service unit 3-part »FUTURA« with metal container, Viewing tube and pressure gauge, Size 2, G 1/2, Control range 0.5-10 bar, Semi  
Three-piece service units with excellent flow rates in modern design.  
Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

### Tehnične Specifikacije

|                                |                                                                         |
|--------------------------------|-------------------------------------------------------------------------|
| Min. temperaturno območje [°C] | -10                                                                     |
| Element filtra                 | Cellpor (PE)                                                            |
| Membrane                       | NBR                                                                     |
|                                | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar |
| Merjenje pretoka               | G 1/2                                                                   |
| Navoj                          | Semi-automatic                                                          |
| Odtok kondenzata               | PA66 GF60                                                               |
| Ohišje                         | Metal container with viewing tube                                       |
| Posoda                         | Material: Die-cast zinc                                                 |
| Priključni navoj               | FUTURA                                                                  |
| Serijska                       | Compressed air, neutral gases                                           |
| Srednje                        | NBR                                                                     |
| Tesnilo                        | PC                                                                      |
| Vidna kupola                   |                                                                         |
| Min. krmilno območje [bar]     | 0.5                                                                     |
| Min. vhodni tlak [bar]         | 1.5                                                                     |
| Velikost                       | 2                                                                       |
| Rang filtra [µm]               | 5                                                                       |
| Max. krmilno območje [bar]     | 10                                                                      |
| Max. vhodni tlak [bar]         | 16                                                                      |
| Zaslon manometra max. [bar]    | 16                                                                      |
| Max. temperaturno območje [°C] | 50                                                                      |
| C [mm]                         | 110.0                                                                   |
| A [mm]                         | 189.0                                                                   |
| B [mm]                         | 261.0                                                                   |
| Pretok [l/min]                 | 3500                                                                    |