

Datum: 12.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## Serv. enota 3-delna »FUTURA-mali« PC zbir.G 1/4, 0.5-10 bar

Kategorija: [Service unit, 3-piece with polycarbonate bowl](#)  
Šifra: **142486RIE**

### Kratek opis

Service unit 3-part »FUTURA-mini«, PC container, Standard pressure gauge, Size 0, G 1/4, Control range 0.5 - 10 bar, Fully-auto.

Three-piece service units with excellent flow rates in modern design.

Diaphragm pressure regulator with secondary ventilation.

### Tehnične Specifikacije

|                                |                                                                         |
|--------------------------------|-------------------------------------------------------------------------|
| Min. temperaturno območje [°C] | -10                                                                     |
| Element filtra                 | Cellpor (PE)                                                            |
| Membrane                       | NBR                                                                     |
|                                | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar |
| Merjenje pretoka               | G 1/4                                                                   |
| Navoj                          | Fully-automatic                                                         |
| Odtok kondenzata               | PA66 GF60                                                               |
| Ohišje                         | Polycarbonate                                                           |
| Posoda                         | container                                                               |
| Priključni navoj               | Plastic                                                                 |
| Serijska                       | FUTURA-mini                                                             |
| Srednje                        | Compressed air, neutral gases                                           |
| Tesnilo                        | NBR                                                                     |
| Vidna kupola                   | PC                                                                      |
| Min. krmilno območje [bar]     | 0.5                                                                     |
| Min. vhodni tlak [bar]         | 1.5                                                                     |
| Rang filtra [µm]               | 5                                                                       |
| Max. krmilno območje [bar]     | 10                                                                      |
| Max. vhodni tlak [bar]         | 12                                                                      |
| Zaslona manometra max. [bar]   | 16                                                                      |
| Max. temperaturno območje [°C] | 50                                                                      |
| C [mm]                         | 63.0                                                                    |
| A [mm]                         | 129.0                                                                   |
| B [mm]                         | 206.0                                                                   |
| Pretok [l/min]                 | 800                                                                     |