



(slika je simbolična)

Serv. enota 3-delna »FUTURA« PC, Vel.2, G 1/2, 0.1-2 Avt.

Kategorija: [Service unit, 3-piece with PC bowl and bowl guard](#)
Šifra: **152649RIE**

Kratek opis

Service unit 3-part »FUTURA« with PC container, Protective cage and pressure gauge, Size 2, G 1/2, Control range 0.1-2 bar, Fully

Three-piece service units with excellent flow rates in modern design.

Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Membrane	NBR
	At $P_1 = 10$ bar, $P_2 = 6.3$
Merjenje pretoka	bar and pressure drop
	$\Delta_p = 1$ bar
Navoj	G 1/2
Odtok kondenzata	Fully-automatic
Ohišje	PA66 GF60
Posoda	Polycarbonate container with protective cage
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Vidna kupola	PC
Min. krmilno območje [bar]	0.1
Min. vhodni tlak [bar]	1.5
Max. krmilno območje [bar]	2
Velikost	2
Zaslon manometra max. [bar]	2.5
Rang filtra [µm]	5
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
C [mm]	110.0
A [mm]	189.0
B [mm]	273.0
Pretok [l/min]	3500