



## **Serv. enota 3-delna »G«PC zbir.5 µmVel. 400G 3/8**

Kategorija: [Service unit, 3-piece with PC bowl, bowl guard](#)  
Šifra: **116424RIE**

(slika je simbolična)

### **Kratek opis**

Service unit 3-part »G«, PC container, Protective cage, 5 µm, Size 400, G 3/8, Input pressure max. 10 bar, Control range 1.5-9 bar  
Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

### **Tehnične Specifikacije**

|                              |                                                                      |
|------------------------------|----------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 3/8                                                                |
| Odtok kondenzata             | Fully-automatic                                                      |
| Ohišje                       | Die-cast aluminium                                                   |
| Posoda                       | Polycarbonate container with protective cage                         |
| Serijska                     | G                                                                    |
| Tesnilo                      | NBR                                                                  |
| Vidna kupola                 | Brass/POM                                                            |
| Vzmet pokrova motorja        | POM                                                                  |
| Min. krmilno območje [bar]   | 1.5                                                                  |
| Rang filtra [µm]             | 5                                                                    |
| Max. krmilno območje [bar]   | 9                                                                    |
| Max. vhodni tlak [bar]       | 10                                                                   |
| C [mm]                       | 48.0                                                                 |
| Max. sobna temperatura [°C]  | 70                                                                   |
| Max. temperatura medija [°C] | 70                                                                   |
| D [mm]                       | 166.5                                                                |
| B [mm]                       | 214.5                                                                |
| A [mm]                       | 236.0                                                                |
| Velikost                     | 400                                                                  |
| Pretok [l/min]               | 2950                                                                 |