



Serv. enota 3-delna »G«PC zbir.5 µmVel. 400G 3/8

Kategorija: [Service unit, 3-piece with PC bowl, bowl guard](#)
Šifra: **116423RIE**

(slika je simbolična)

Kratek opis

Service unit 3-part »G«, PC container, Protective cage, 5 µm, Size 400, G 3/8, Input pressure max. 10 bar, Control range 1.5-9 bar
Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast aluminium
Posoda	Polycarbonate container with protective cage
Serija	G
Tesnilo	NBR
Vidna kupola	Brass/POM
Vzmet pokrova motorja	POM
Min. krmilno območje [bar]	1.5
Rang filtra [µm]	5
Max. krmilno območje [bar]	9
Max. vhodni tlak [bar]	10
C [mm]	48.0
Max. sobna temperatura [°C]	70
Max. temperatura medija [°C]	70
D [mm]	166.5
B [mm]	214.5
A [mm]	236.0
Velikost	400
Pretok [l/min]	2950