



Serv. enota 3-delna »variobloc« z PC zbir.Vel.2,G 1/2

Kategorija: [Service unit, 3-piece with polycarbonate bowl](#)
Šifra: **100714RIE**

(slika je simbolična)

Kratek opis

Service unit 3-part »variobloc« with PC container, Size 2, G 1/2, Input pressure max. 16 bar, Medium / ambient temp. max. 50 °C

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

Membrane	NBR
Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/2
Odtok kondenzata	Manual
Ohišje	Die-cast zinc
Posoda	Polycarbonate container
Serijska	variobloc
Tesnilo	NBR
Vidna kupola	PA
Vzmet pokrova motorja	POM
Min. krmilno območje [bar]	0.5
Velikost	2
Max. krmilno območje [bar]	10
Zaslon manometra max. [bar]	10
Max. vhodni tlak [bar]	16
Rang filtra [μ m]	40
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
C [mm]	98.0
A [mm]	210.0
B [mm]	274.0
Pretok [l/min]	3400