



(slika je simbolična)

Servisna enota 2-delna »Stinard-mali« s kovinsko posodo, G 1/8

Kategorija: [Service unit, 2-piece with metal bowl](#)
Šifra: **100799RIE**

Kratek opis

Service unit 2-part »Standard-mini«, Metal container, pressure gauge, G 1/8, Input pressure max. 25 bar, Control range 0.5-10 bar
Compact, two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8 \text{ bar}$, $P_2 = 6 \text{ bar}$ and pressure drop $\Delta p = 1 \text{ bar}$
Navoj	G 1/8
Odtok kondenzata	Manual
Ohišje	Die-cast zinc, painted silver
Posoda	Metal container
Serijska	Standard-mini
Tesnilo	NBR
Vidna kupola	Zinc-glass-NBR
Min. krmilno območje [bar]	0.5
DN	5
Rang filtra [μm]	5
Max. krmilno območje [bar]	10
Zaslona manometra max. [bar]	16
Max. vhodni tlak [bar]	25
Max. sobna temperatura [$^{\circ}\text{C}$]	60
Max. temperatura medija [$^{\circ}\text{C}$]	60
C [mm]	65.0
A [mm]	85.0
D [mm]	98.5
B [mm]	163.5
Pretok [l/min]	350