



Servisna enota VARNOSTNA »FUTURA«, Velikost 1, G 3/8

Kategorija: [SAFETY service unit set](#)
Šifra: **100268RIE**

(slika je simbolična)

Kratek opis

Service station SAFETY »FUTURA«, Ball valve - start-up valve - 2-part service unit, Size 1, G 3/8, Input pressure 2.5 - 16 bar

These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Membrane	NBR
	At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar
Merjenje pretoka	G 3/8
Navoj	Fully-automatic
Odtok kondenzata	Silencer (ball valve)
Odzračevalni vtič	PA66 GF60
Ohišje	Material: Die-cast zinc
Priključni navoj	FUTURA
Serijska	Compressed air, neutral gases
Srednje	NBR
Tesnilo	1
Velikost	2.5
Min. krmilno območje [bar]	2.5
Min. vhodni tlak [bar]	5
Rang filtra [µm]	8
Max. krmilno območje [bar]	10
Zaslon manometra max. [bar]	16
Max. vhodni tlak [bar]	50
Max. temperaturno območje [°C]	96.0
C [mm]	208.0
A [mm]	243.0
B [mm]	1750
Pretok [l/min]	