



(slika je simbolična)

Servisna enota VARNOSTNA »multifix«, Velikost 1, G 1/4

Kategorija: [SAFETY service unit set](#)
Šifra: **100602RIE**

Kratek opis

Service station SAFETY »multifix«, Ball valve - start-up valve - 2-part service unit, Size 1, G 1/4, Input pressure 2 - 16 bar. These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

Tehnične Specifikacije

Element filtra	Cellpor (PE)
Membrane	NBR
	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Merjenje pretoka	G 1/4
Navoj	Semi-automatic
Odtok kondenzata	Silencer (ball valve)
Odzračevalni vtič	Die-cast zinc
Ohišje	multifix
Serijska	Compressed air
Srednje	NBR
Tesnilo	POM
Vzmet pokrova motorja	1
Velikost	2
Min. krmilno območje [bar]	2
Min. vhodni tlak [bar]	5
Rang filtra [μ m]	10
Max. krmilno območje [bar]	16
Max. vhodni tlak [bar]	16
Zaslon manometra max. [bar]	60
Max. temperaturno območje [°C]	94.0
C [mm]	182.8
B [mm]	219.1
A [mm]	1000
Pretok [l/min]	