

Datum: 12.05.2024



(slika je simbolična)

Sesalna šalčka meh, okrogla 1.5 pregib, Material NBR, »FGA« Ø20

Kategorija: [Bellows suction pad, round, 1.5 folds, NBR](#)
Šifra: **108493RIE**

Kratek opis

Bellows suction cup, Round 1.5 folds, Material NBR, »FGA«, Ø 20 mm, suitable connection nipple IT G 1/8, ET M5 / G 1/8
Robust and hard-wearing suction pad with a single sealing lip.

Used wherever objects (parts, packing materials, etc.) need to be lifted, transported, turned over or handled in some other manner. It is also ideal when it is necessary to compensate varying workpiece heights or uneven surfaces or to handle easily damaged parts. It acts as the connecting element between the vacuum generator and the workpiece.

Properties:

- Very stiff top fold
- Soft, tapered sealing lips
- Supports on the bottom
- High suction force
- Optimum damping effect
- Very good adaptation to curved workpiece surfaces or materials with uneven surfaces

Applications:

- Handling workpieces with extremely uneven surfaces (e.g. pipes)
- Handling easily damaged parts

Tehnične Specifikacije

Primerna povezava priključka z notranjim navojem	M5 / G 1/8
Primerna povezava priključka z zunanjim navojem	G 1/8
Prostornina [cm³]	1.150
Ø notranje cevi [mm]	4
Sesalna sila [N]	4.7
Izvlačna sila [N]	10.7
Premier [mm]	20
Višina priključka z notranjim navojem [mm]	20.5 / 21.5
Višina priključka z zunanjim navojem [mm]	27.5
Min. izbočen polmer krivine [mm]	30