



Stainless steel filter regulator 1.4404, rever. G 1/2, 1 - 15 bar

Kategorija: [Stainless steel filter regulators 1.4404](#)
Šifra: **129274RIE**

(slika je simbolična)

Kratek opis

Stainless steel filter regulator, 1.4404, with secondary venting (reversible), incl. press. gauge, G 1/2, Control range 1 - 15 bar

Stainless steel filter regulators with self-relieving (not for liquid media) containing no non-ferrous metals for use in the food processing, chemical, mining, plant construction and special machinery industries as well as in the medical technology.

Tehnične Specifikacije

Membrane	PTFE on NBR carrier At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p \leq 1$ bar
Merjenje pretoka	G 1/2
Navoj	Manual drain valve
Odtok kondenzata	Stainless steel
Ohišje	1.4404 (AISI 316L)
Tesnilo	FKM
Min. krmilno območje [bar]	1
Max. krmilno območje [bar]	15
Max. vhodni tlak [bar]	30
Rang filtra [μ m]	50
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	80
A [mm]	109.0
C [mm]	121.0
B [mm]	246.0
Pretok [l/min]	3000