



(slika je simbolična)

## Standardni manometer, prikllop spodaj, G 1/4, 0 - 25 bar, Ø 63

Kategorija: [Wika](#)  
Šifra: **101718RIE**

### Kratek opis

Standard pressure gauge, Single scale bar, Connection radial bottom, G 1/4, Goods class 1.6, Measurement range 0 - 25 bar, Ø 63  
Bourdon-tube pressure gauge in standard design.  
Suitable for gaseous or liquid media which do not corrode copper alloy,  
do not have high viscosity and do not crystallise.

### Tehnične Specifikacije

|                                            |                     |
|--------------------------------------------|---------------------|
| Min. sobna temperatura [°C]                | -20                 |
| Min. temperatura medija [°C]               | -20                 |
| Material Prozessanschluss                  | Copper alloy        |
| Merilni element                            | Copper alloy        |
| Ohišje                                     | Plastic             |
| Položaj povezave                           | radial on bottom    |
| Povezava                                   | G 1/4               |
| Prednje steklo                             | Transparent plastic |
| Premikanje                                 | Copper alloy        |
| Spodnja/Zgornja meja območja               | Positive pressure   |
| Stopnja rasti na območju skale - bar [bar] | 1                   |
| Razred točnosti                            | 1.6                 |
| Merilno območje max. bar                   | 25                  |
| Max. sobna temperatura [°C]                | 60                  |
| Max. temperatura medija [°C]               | 60                  |
| Premier [mm]                               | 63                  |
| Vrsta                                      | 111.10              |