



(slika je simbolična)

## Stenski priključek z dvojno hitrospojko I.D. 7.2

Kategorija: [Distributor socket with quick disconnect coupl. DN 7.2](#)  
Šifra: **107275RIE**

### Kratek opis

End distributor socket, with 2 standard couplings I.D. 7.2, input G 1/2, Operat. pressure max. 15bar, Ambient temp. -10°C to 50°C2 or 3-way distributor sockets made of high-strength glass fibre-reinforced plastic (PA6 GF 30) for a wide range of applications. Available with 2 or 3 pre-assembled, brass quick disconnect couplings and 2 inlet thread sizes for input and output threads (Not combinable). All distributor sockets have a durable brass threaded insert, whose shape secures it against rotation and against axial shift due to its shape. Drilling diagram dimensions are identical for all distributor sockets, so a simpler and more flexible exchange replacement. Caution: Note that the distributor sockets should not be installed in danges zones. Danger zones are, for example, transport routes, escape routes, etc.

### Tehnične Specifikacije

|                                                 |                                          |
|-------------------------------------------------|------------------------------------------|
| Dovodni navoj                                   | G 1/2                                    |
| Material navojev                                | Brass                                    |
| Ohišje                                          | Glass fibre-reinforced plastic PA6 GF 30 |
| Spojka                                          | 2 x brass coupling                       |
| Max. moment privijanja - pritrdilne luknje [Nm] | 4                                        |
| Max. moment privijanja - medeninasta nit [Nm]   | 12                                       |
| Max. obratovalni tlak [bar]                     | 15                                       |
| Višina [mm]                                     | 59.0                                     |
| Premer [mm]                                     | 120.0                                    |