

Datum: 11.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



Stropni nosilec s hN.N.rim priključkom I.D. 7.2G 3/8 N.N.

Kategorija: [Wall plate with quick disconnect coupling DN 7.2](#)
Šifra: **107273RIE**

(slika je simbolična)

Kratek opis

Ceiling bracket with quick-connect coupling I.D. 7.2, Bright brass, G 3/8 IT, Operating pressure 0-35 bar, Temp. -20 °C to 100 °C

1, 2 or 3-way distributor pieces made of brass with a bare metal surface, pre-assembled with quick disconnect coupling DN 7.2.

Available with threaded connection inside or outside or nipple for adaptation into an existing quick disconnect coupling DN 7.2 to DN 7.8.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Ohišje	Brass with a bare metal surface
Povezava	G 3/8 IT
Spojke	DN 7.2, brass with a bare metal surface, G 3/8 ET
Tesnilo	Industrial adhesives, medium strength
Varovaka	Industrial adhesives, medium strength
Sestava distributerja	2 x G 3/8 IT
Max. obratovalni tlak [bar]	35
Premer [mm]	39.0
Višina [mm]	40.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100