

Datum: 11.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## T-obroč kos za votli vijak G 1/8, za cev zunanja Ø 6 mm

Kategorija: [T-ring nipple](#)  
Šifra: **108845RIE**

### Kratek opis

T-ring piece, for hollow screw G 1/8, for hose exterior Ø 6 mm, Working pressure -0.98 to 16 bar, Operating temp. -20 °C to 70 °C

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass.

Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

### Tehnične Specifikacije

|                               |                     |
|-------------------------------|---------------------|
| Min. delovna temperatura [°C] | -20                 |
| Min. delovni tlak [bar]       | -0.98               |
| Material                      | Nickel-plated brass |
| Priporočena cev               | PA, PU              |
| Rokav                         | POM black           |
| Serijska                      | click-clock         |
| Vpenjalni obroč               | Stainless steel     |
| Za banjo vijak                | G 1/8               |
| Za cevi O.D. [mm]             | 6                   |
| L2 [mm]                       | 15.0                |
| Max. delovni tlak [bar]       | 16                  |
| L1 [mm]                       | 46.0                |
| Max. delovna temperatura [°C] | 70                  |