

Datum: 13.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

T-reducir prik. POM, zun. Ø1 22 mm / Ø2 15 mm

Kategorija: [Union tees, unequal - POM](#)
Šifra: **110327RIE**

Kratek opis

T-reducer connector POM, for hose exterior Ø1 22 mm, for hose exterior Ø2 15 mm, working pressure -0.95 to 10 bar
Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications.

All our push-in fittings made of POM have the following approvals:

drinking water DVGW, KTW, FDA and NSF.

Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Tehnične Specifikacije

Min. delovna temperatura v zraku [°C]	-20
Min. delovni tlak [bar]	-0.95
Material	Acetal polymer (POM)
Min. delovna temperatura v vodi [°C]	1
Max. delovni tlak [bar]	10
Za cevi O.D. 2 [mm]	15
Za cevi O.D. 1 [mm]	22
L2 [mm]	41.6
Max. delovna temperatura v zraku [°C]	65
Max. delovna temperatura v vodi [°C]	70
L1 [mm]	90.6