

Datum: 12.05.2024



(slika je simbolična)

## Tlačni regulator »Stinard-mali«, Velikost 0, G 1/4, 0.5 - 10 bar

Kategorija: [Pressure regulators](#)Šifra: **100768RIE**

### Kratek opis

Pressure regulator »Standard-mini« incl. pressure gauge,  
Size 0, G 1/4, Input pressure max. 25 bar, Control range 0.5  
- 10 bar

Reversible diaphragm pressure regulators with self-relieving  
design in compact design.

The pressure setting can be locked by pushing the knob  
down.

### Tehnične Specifikacije

|                                 |                                                                            |
|---------------------------------|----------------------------------------------------------------------------|
| Merjenje pretoka                | At $P_1 = 8$ bar, $P_2 = 6$<br>bar and pressure drop<br>$\Delta p = 1$ bar |
| Navoj                           | G 1/4                                                                      |
| Ohišje                          | Die-cast zinc, painted<br>silver                                           |
| Serijska                        | Standard-mini                                                              |
| Tesnilo                         | NBR/TPU                                                                    |
| Vzmet pokrova motorja           | POM-brass                                                                  |
| Min. krmilno območje [bar]      | 0.5                                                                        |
| DN                              | 5                                                                          |
| C [mm]                          | 9.5                                                                        |
| Max. krmilno območje [bar]      | 10                                                                         |
| Zaslon manometra max.<br>[bar]  | 16                                                                         |
| Max. vhodni tlak [bar]          | 25                                                                         |
| A [mm]                          | 43.0                                                                       |
| Max. sobna temperatura<br>[°C]  | 60                                                                         |
| Max. temperatura medija<br>[°C] | 60                                                                         |
| D [mm]                          | 63.0                                                                       |
| B [mm]                          | 72.5                                                                       |
| Pretok [l/min]                  | 340                                                                        |