

Datum: 13.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Varn. ventil, med., G 2, vkl. prit. 0.3 bar

Kategorija: [Varnostni ventil G 2](#)  
Šifra: **105044RIE**

### Kratek opis

Safety valve, High performance design, Brass, Operating temp. -40 °C to 200 °C, G 2, AF 70, Trigger pressure 0.3 bar  
For compressed air and non-toxic, non-flammable gases, cannot be used for liquids due to free blow-off, not suitable for steam.  
These valves are TÜV approved and have a TÜV type test number.

### Tehnične Specifikacije

|                               |         |
|-------------------------------|---------|
| Min. delovna temperatura [°C] | -40     |
| Navoj                         | G 2     |
| Ohišje                        | Brass   |
| Tesnilo                       | FPM     |
| Tlačna vzmet                  | C steel |
| Min. nastavljeni tlak [bar]   | 0.3     |
| Min. obratovalni tlak [bar]   | 0.5     |
| A [mm]                        | 25.0    |
| Max. obratovalni tlak [bar]   | 26      |
| narediti [mm]                 | 40.0    |
| a/f [mm]                      | 70      |
| Max. delovna temperatura [°C] | 200     |
| H [mm]                        | 203.0   |