



(slika je simbolična)

Varnostna spojka I.D. 7.6»stream line«za cev12x8

Kategorija: [Safety coupling DN 7.6, »stream line«](#)
Šifra: **107601RIE**

Kratek opis

Safety coupling I.D. 7.6, »stream line«, galvanised steel / brass, for hose 12x8, Operating pressure max. 16 bar

High-quality, robust and durable, one-hand quick disconnect safety couplings, with very high flow rates and only a small pressure drop.

The coupling is released fully automatically in two steps. Air is relieved from the coupling before it is completely disconnected. The plug is only disconnected from the coupling if the residual pressure has dropped below 0.3 bar. The dreaded "whiplash effect" is thus avoided and the risk of injury virtually eliminated.

This safety version conforms to ISO-Standard DIN EN ISO 4414.

These safety couplings are not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Areas of application: Pneumatic system, machine and plant engineering, manufacturing industry, workshops, automotive, mining.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material	Steel / zinc-plated brass
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Tesnilo	NBR
Vzmet	Stainless steel
DN	7.6
Za cevi [mm]	12x8
Max. obratovalni tlak [bar]	16
a/f 1 [mm]	19
a/f 2 [mm]	20
Dolžina [mm]	68.1
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	2250 l/min (air)