

Datum: 13.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Varnostne Čeljustna spojka s cevnim priklj. I.D. 25 (1\")DN 19

Kategorija: [Safety claw coupling, with hose connection](#)
Šifra: **107885RIE**

Kratek opis

Safety jaw coupling with hose connection, I.D. 25 (1\"), DN 19, Malleable cast iron, Operating pressure max. 16 bar
Universal standard coupling in safety design according to DIN 3238 for absolutely secure compressed air lines on construction sites or in industry.
Easy to couple, secured against accidental opening: just screw the ring tight after coupling!
- Robust couplings with malleable iron head, steel stem with special profile,
zinc plated and yellow chromated
- Chrome VI-free, with double safety lock
- Large bore for increased flow rate

Tehnične Specifikacije

Min. delovna temperatura [°C]	-40
Material	Malleable iron
Tesnilo	NBR
Za cev I.D.	"25 (1\"")"
Max. obratovalni tlak [bar]	16
DN	19
Razdalja med objemkami [mm]	42
H [mm]	63.0
L [mm]	86.6
Max. delovna temperatura [°C]	95