

Datum: 13.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Varnostni krogelni ventil brez zaklepa, z izpustom, Rp 1/2

Kategorija: [Safety ball valves non-lockable, with relief port](#)
Šifra: **103255RIE**

Kratek opis

Safety ball valve, not lockable, with venting hole, nickel-plated brass, Operating temp. max. 60°C, Rp 1/2, DN 15, PN max. 12 bar
Brass safety ball valves.
Specially designed for pneumatic applications.
The ball valve shuts off the supply side and relieves the application into the atmosphere.

Tehnične Specifikacije

Krogla	Nickel-plated brass
Material navojev	Brass with a bare metal surface
Navoj	Rp 1/2
Ohišje	Nickel-plated brass
Ročica	Die-cast aluminium, black
Standardni navoj	Rp thread acc. to ISO 7-1
Steblo	Nickel-plated brass
Škatla za polnjenje	Nickel-plated brass
Tesnilo	PTFE
Max. obratovalni tlak [bar]	12
DN	15
Max. delovna temperatura [°C]	60
B [mm]	64.0
L [mm]	69.0
A [mm]	100.0