



Vhod.plošča za vent. terminal HDM,zun. zračni nadzor,Profibus DP

Kategorija: [Metalwork](#)
Šifra: **106673RIE**

(slika je simbolična)

Kratek opis

Input plate for valve terminal HDM, with external control air, with integrated Profibus DP, Working pressure vacuum up to 10 bar

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates.

Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Monostable (non-latching) version of manual control also available on request.

The operating pressure is based on the installed input plates.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Min. obratovalni tlak [bar]	-1
Ffunkcija	with external control air, vacuum up to 10 bar
IP zaščita	IP 65
Material	aluminium
Poskusno	Max. 16 (e.g. 16 spring return valves)
Povezava	With integrated Profibus DP
Ročno upravljanje	latching
Vhodna moč	0.6 W per pilot
Max. obratovalni tlak [bar]	10
Max. temperaturno območje [°C]	60