

Datum: 13.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Vklopni ventil »multifix-mali«, Velikost 0, G 1/4

Kategorija: [Start-up valve](#)
Šifra: **100414RIE**

Kratek opis

Start up valve »multifix-mini«, Size 0, G 1/4, Input pressure min. 2.5 bar, max. 16 bar, Medium / ambient temperature max. 60 °C
Seat valves operated by secondary pressure for controlled pressurisation of pneumatic systems.
The full cross-section of the regulator is opened at 50% of the input pressure.
With adjustable restrictor!

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/4
Ohišje	Die-cast zinc
Serijska	multifix-mini
Tesnilo	NBR
Min. vhodni tlak [bar]	2.5
Max. vhodni tlak [bar]	16
D [mm]	29.0
A [mm]	45.0
C [mm]	48.5
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
B [mm]	77.5
Pretok [l/min]	2250