

Datum: 12.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



## Vklopni ventil »multifix« z nastavljivim gumbom, Velikost 5, G 1

Kategorija: [Start-up valves](#)  
Šifra: **100629RIE**

(slika je simbolična)

### Kratek opis

Start up valve »multifix«, with adjustable throttle, Size 5, G 1, Input pressure 2 - 16 bar, Medium / ambient temp. max. 60 °C

Seat valves operated by secondary pressure for controlled pressurisation of pneumatic systems.

The full cross-section of the regulator is opened at 50% of the input pressure.

The filling time can be altered by turning the adjusting screw.

### Tehnične Specifikacije

|                              |                                                             |
|------------------------------|-------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 6$ bar and<br>pressure drop $\Delta p = 1$<br>bar |
| Navoj                        | G 1                                                         |
| Ohišje                       | Aluminium                                                   |
| Serijska                     | multifix                                                    |
| Tesnilo                      | NBR                                                         |
| Min. vhodni tlak [bar]       | 2                                                           |
| Velikost                     | 5                                                           |
| Max. vhodni tlak [bar]       | 16                                                          |
| D [mm]                       | 52.0                                                        |
| Max. sobna temperatura [°C]  | 60                                                          |
| Max. temperatura medija [°C] | 60                                                          |
| A [mm]                       | 99.7                                                        |
| B [mm]                       | 104.0                                                       |
| Pretok [l/min]               | 16000                                                       |